## **AMENDMENTS TO THE CLAIMS**

Docket No.: 05581-00145-US

- 1. (Original) Mono or multilayered polypropylene cast film comprising at least one layer wherein said at least one layer comprises a two component polymer composition of a first component I and a second component II, characterised in that the first component I is a high crystallinity propylene homopolymer and the second component II is a heterophasic propylene copolymer.
- 2. (Original) Cast film according to claim 1, characterized in that the high crystallinity propylene homopolymer has a stereoregularity of 94 to 99%.
- 3. (Original) Cast film according to claim 2 characterised in that, the high crystallinity propylene homopolymer contains 98 to 100% by weight of propylene units.
- 4. (Currently amended) Cast film according to claim 1 or 2 characterised in that, the high crystallinity propylene homopolymer has a melt flow index of 5 to 10 g/10min and a melting point of 150 to 170°C.
- 5. (Currently amended) Cast film according to any of the preceding claims, characterised in that, the high crystallinity propylene homopolymer contains 1,5 to 5% 1.5 to 5% by weight of xylene solubles.
- 6. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, heterophasic propylene copolymer comprises a propylene homopolymer matrix and a dispersed elastomeric rubber phase.
- 7. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the heterophasic propylene copolymer contains 12 to 18% by weight of xylene solubles.
- 8. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the heterophasic propylene copolymer has an ethylene content of 5 to 15% by weight, based on the weight of the heterophasic propylene copolymer

  456853

  3

P

9. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the heterophasic propylene copolymer has a melt flow index of 0,2 index of 0.2 to 5g/10min.

Docket No.: 05581-00145-US

- 10. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the heterophasic propylene copolymer has a Vicat softening point of 145 to 155°C.
- 11. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the heterophasic propylene contains less than 5 20% by weight of the elastomeric rubber phase, based on the weight of the heterophasic propylene copolymer
- 12. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the dispersed elastomeric rubber phase is a ethylene propylene copolymer.
- 13. (Currently amended) Cast film according to any of the preceding claims claim 12, characterised in that, the ethylene propylene copolymer rubber has an ethylene ethylene content of 40 to 65%.
- 14. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the two component polymer composition is a mixture of the two components.
- 15. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the two component polymer composition is a blend of the two components.
- 16. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the ratio of the two components I and II is in the range of from high crytallinity polypropylene (HCPP) to heterophasic propylene copolymer (HP),

HCPP:HP = 90:10 to 50:50.

17. (Currently amended) Cast film according to elaim claim 16, wherein said ratio is in the range from HCPP:HP = 80:20 to 60:40.

456853 4

18. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the base layer contains 80 to 100% by weight of the two components polymer composition, based on the weight of the layer.

Docket No.: 05581-00145-US

- 19. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the base layer containing the two components polymer composition is at least 50% of the overall film thickness. thickness.
- 20. (Currently amended) Cast film according to any of the preceding claim claim 1, characterised in that, a second layer containing 80 to 100% by weight of the two component polymer composition is provided on the first surface of the base layer.
- 21. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, a third layer containing 80 to 100% by weight of the two component polymer composition is provided on the second surface of the base layer.
- 22. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, one or two intermediate layers are provided between the outer layers and the base layer.
- 23. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the base layer contains 1000 to 3000 ppm 500 to 5000 ppm of a nucleating agent.
- 24. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, both cover layers contain an antistatic agent and a slip agent.
- 25. (Currently amended) Cast film according to any of the preceding claims claim 1, characterised in that, the antistatic agent is glycerol monostearate and the slip agent is oleamid and/or stereoamid.
- 26. (Currently amended) Label made from a cast film according to any of the preceding claims claim 1.

456853 5

- 27. cancelled
- 28. cancelled
- 29. (New) A mold labelling process which comprises using of the label according to claim 26 and wherein the container is formed by injection moulding.

Docket No.: 05581-00145-US

30. (New) A mold labelling process which comprises using of the label according to claim 26 and wherein the container is formed by blow molding.

456853